

**Mechanical characteristics**  
cables

interface dimensions acc. to assembly instruction  
centre conductor  
outer conductor  
mating life

**Components**  
centre conductor  
crimp ferrule  
other metal parts  
insulator  
gasket

**Electrical characteristics**  
impedance  
frequency  
return loss  
insertion loss  
voltage proof  
contact resistance  
centre contact  
outer contact

**Environmental**  
operating temp.  
RoHS compliant

**Mechanische Eigenschaften**  
Kabel

Steckgesicht nach Montageanleitung  
Innenleiter  
Außenleiter  
Steckzyklen

**Bauteile**  
Innenleiter  
Crimprohr  
sonstige Metallteile  
Isolierung  
Dichtung

**Elektrische Eigenschaften**  
Wellenwiderstand  
Frequenz  
Rückflussdämpfung  
Einfügedämpfung  
Prüfspannung  
Kontaktwiderstand  
Innenkontakt  
Außenkontakt

**Umgebung**  
Betriebstemperatur  
RoHS konform

G 1: 7806A Belden, 9907 Belden, CNT-195 Andrew, HPF 195 Harbour Industries, KX 15, LMR-195 TMS, RG-58C/U, WCX195 NEK/CDT

IEC 61169-54  
B4205  
crimp  
crimp  
>100



**Materials / Material**  
brass / Messing  
copper / Kupfer  
brass / Messing  
PTFE  
silicone

**Finish / Oberfläche**  
Cu2Ag5  
CuSnZn3  
CuSnZn3

50  $\Omega$   
0-6 GHz  
typ.: 1 GHz - 38 dB; 2.5 GHz - 30 dB  
1 GHz - <0,05 dB; 2.5 GHz - <0,08 dB  
1.0 kV<sub>eff</sub> / 50 Hz

$\leq 1 \text{ m}\Omega$   
 $\leq 0,5 \text{ m}\Omega$

-40°C / 85°C  
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]	
					10.07.2017	HR		
				gepr./ appr.	12.07.2017	KL	ca./approx.	30
				Maßstab/ scale	Benennung/ title			
				2:1	4.3-10 Straight Plug Push Pull 4.3-10 Kabelstecker Push Pull			
				untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.		
					K	J01440A3028		
				Ersatz für/ replaces				
								
								 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1