



**Mechanical characteristics**

cables  
assembly code  
panel piercing

**Mechanische Eigenschaften**

Kabel  
Montageanleitung  
Montagebohrung

G 3: KX 21A, RG-178B/U, RG196A/U  
D0313  
Z026

**Components**

body  
crimp ferrule

**Bauteile**

Körper  
Crimprohr

**Materials / Material**

CuZn39Pb3  
Cu SF w

**Finish / Oberfläche**

Cu1-2Ni-2Sn3-6 matt  
Ni5

**Electrical characteristics**

impedance

**Elektrische Eigenschaften**

Wellenwiderstand

50 Ω

**Environmental**

RoHS compliant

**Umgebung**

RoHS konform

2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]	
				gepr./ appr	06.11.2019	MA		
							ca./approx. 0,5	
Maßstab/ scale 5:1 (1:1)				Benennung/ title <b>Cable Terminator for PCB Kabeldirektanschluss für LTP</b>				
untol. Maße/ dim. without tolerances according to				Untert./ doc. type <b>K</b>	Zeichnungsnr./ drawing no. <b>H01000A0047</b>			
Ersatz für/ replaces								Blatt/ sheet 1 von/ of 1