

Mechanical characteristics
cables

interface dimensions acc. to assembly code
center conductor
outer conductor
mating life
coupling torque

Components

center conductor
outer conductor
other metal parts
insulator
gasket

Electrical characteristics

impedance
voltage proof
insulation resistance
contact resistance
center contact
outer contact

Environmental

operating temp.
protection class
RoHS compliant

Mechanische Eigenschaften
Kabel

Steckgesicht nach Montageanleitung
Innenleiter
Außenleiter
Steckzyklen
Kupplungsdrehmoment

Bauteile

Innenleiter
Außenleiter
sonstige Metallteile
Isolierung
Dichtung

Elektrische Eigenschaften

Wellenwiderstand
Prüfspannung
Isolationswiderstand
Durchgangswiderstand
Innenkontakt
Außenkontakt

Umgebung

Betriebstemperatur
Schutzklasse
RoHS konform

G30: 02YS(ST)CY 1.4/3.7-50 LI Leoni;
1.4/3.8 AF Draka; 7808A Belden;
CNT-240 Andrew; MRC 240 AFB Draka;
HPF 240 Harbour Industries; LMR-240 TMS;
S 04172 D Suhner; SX 04172 B-60 Suhner;
Speedfoam 240 HFJ Habia,
TZC 500 25 Ericsson; WCX240 NEK/CDT


IEC 61169-54
D11
solder / löt
clamp / klemm
>100
5 Nm

Materials / Material

CuZn39Pb3
CuZn39Pb3
CuZn39Pb3
PTFE
silicone / Silikon

Finish / Oberfläche



Cu2Ag5
CuSnZn3
CuSnZn3



50 Ω
2,5 kV_{eff} / 50 Hz
≥ 5 GΩ

≤ 1 mΩ
≤ 1 mΩ

-40°C / +85°C
IP67 (IEC 60529)
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name		Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn		13.02.2019	MA	
			gepr./ appr.		19.02.2019	BJ	ca./approx. 79
Maßstab/ scale				Benennung/ title			
1:1				4.3-10 Angle Plug 4.3-10 - Kabelwinkelstecker			
untol. Maße/ dim. without tolerances according to				Untert./ doc. type		Zeichnungsnr./ drawing no.	
				K		J01440A0036	
Ersatz für/ replaces							
							
				 Maße/ dimensions: mm			
				Original : DIN A4			
				Blatt/ sheet 1 von/ of 1			