

**Mechanical characteristics**

cables

interface dimensions acc. to assembly instruction

centre conductor

outer conductor

mating life

**Components**

centre contact

outer contact

other metal parts

insulator

o-ring

**Electrical characteristics**

impedance

frequency

return loss

voltage proof

**Environmental**

operating temp.

RoHS compliant

**Mechanische Eigenschaften**

Kabel

Steckgesicht nach Montageanleitung

Innenleiter

Außenleiter

Steckzyklen

**Bauteile**

Innenkontakt

Außenkontakt

sonstige Metallteile

Isolierung

O-Ring

**Elektrische Eigenschaften**

Wellenwiderstand

Frequenz

Rückflussdämpfung

Prüfspannung

**Umgebung**

Betriebstemperatur

RoHS konform

G30 (1.5/3.8):

02YS(ST)CY 1.4/3.7-50 LI, 1.4/3.8 AF, 7808A, CNT-240,

HPF 240, KSR240, LMR-240, MRC 240 AFB,

S 04172 D, SPEEDFOAM 240 HFJ, SX 04172 B-60,

TZC 500 25, WCX240

1.5-3.5

A5631

crimp

crimp

>100

**Material / Material**

brass/ Messing

brass/ Messing

brass/ Messing

PTFE

silicone


**Finish / Oberfläche**



Cu2Ag5

CuSnZn3

CuSnZn3

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]		
			gez./ drawn	06.10.2020	SST			
			gepr./ appr.	14.10.2020	GB	ca./approx. 7,5		
Maßstab/ scale			Benennung/ title					
2:1 (1:1)			1.5-3.5 Straight Plug, Screw 1.5-3.5 Kabelstecker, Screw					
untol. Maße/ dim. without tolerances according to			Untert./ doc. type	Zeichnungsnr./ drawing no.				 Maße/ dimensions: mm
			K	J01480A0007				
			Ersatz für/ replaces	EWC00095-00				Original : DIN A4
							Blatt/ sheet 1 von/ of 1	