


Z113
panel piercing
Montagebohrung



Mechanical characteristics
cable group

interface dimensions acc. to assembly code
center conductor
outer conductor
mating life
coupling torque

Components
center contact
outer contact
other metal parts
insulator

Electrical characteristics
impedance
frequency
return loss

voltage proof
insulation resistance
contact resistance
center contact
outer contact

Environmental
operating temp.
RoHS compliant

Mechanische Eigenschaften

Kabelgruppe

Steckgesicht nach Montageanleitung
Innenleiter
Außenleiter
Steckzyklen
Kupplungsdrehmoment

Bauteile
Innenkontakt
Außenleiter
sonstige Metallteile
Isolierung

Elektrische Eigenschaften
Wellenwiderstand
Frequenz
Rückflusdämpfung

Prüfspannung
Isolationswiderstand
Durchgangswiderstand
Innenkontakt
Außenkontakt

Umgebung

Betriebstemperatur
RoHS konform

G 4 (RG-179B/U) : 0.3LS/1.7S, 1520A BELDEN (RGB-Kabel), 1521A BELDEN (RGB-Kabel), 1522A BELDEN (RGB-Kabel), 179DT BELDEN Precision Video Cable, RG-179B/U, RG-187A/U

IEC 61169-24
A4541
solder /löt
crimp
>500
46-69 Ncm

Materials / Material
brass / Messing
brass / Messing
brass / Messing
PTFE

Finish / Oberfläche
gold plated / vergoldet
nickel plated / vernickelt
nickel plated / vernickelt

75 Ω
0-3 GHz
typ.: 1 GHz-30 dB; 2 GHz-22 dB;
3 GHz-18 dB; 4 GHz-16 dB
750 V_{eff} / 50 Hz
≥ 1 GΩ
≤ 5 mΩ
≤ 2,5 mΩ

-40°C / +155°C
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]
					24.06.2015	MA	
				gepr./ appr.	01.07.2015	KL	ca./approx.
				Maßstab/ scale	Benennung/ title		
				2:1	F Bulkhead Jack F-Kabeleinbaubuchse		
				untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	
					K	J01601A0008	
b	31833	15.12.2020	BJ				
a	30768	18.09.2019	KL				
				Ersatz für/ replaces			
						Maße/ dimensions: mm	
						Original : DIN A4	
						Blatt/ sheet 1 von/ of 1	